

Effect of Rotation on Couple Stress Ferromagnetic Micropolar Fluid Heated from Below in Porous Medium

Sushila¹ and Dr. Naveen Sharma²

¹Department of Mathematics, DAV College, Muzaffarnagar. CCS University, Meerut, INDIA.

²Professor, Department of Mathematics DAV College, Muzaffarnagar CCS University, Meerut, INDIA.

¹Corresponding Author: sushilagill16@gmail.com



www.jrasb.com || Vol. 4 No. 1 (2025): February Issue

Received: 13-02-2025

Revised: 19-02-2025

Accepted: 24-02-2025

ABSTRACT

The linear stability analysis of heat convection in a rotating couple stress ferromagnetic micropolar fluid layer, heated from below and suspended within a porous medium, is the main focus of the current research. The work finds justification in understanding intricate convective processes in systems in which microstructural influence, rotation, magnetism, and porous media interaction occur together—typically occurring in geophysical, industrial, and biomedical processes. A general mathematical model is formulated by combining couple stress theory, Eringen's micropolar fluid theory, and the theory of magnetohydrodynamics. This multi-theory approach encompasses the classical and non-classical behavior of the fluid by incorporating micro-rotational effects, couple stress effects, and the influence of an external magnetic field. The porous medium is treated using Darcy's law, adding the Darcy number to include permeability effects. Rotation is included through the Coriolis force, which is described in terms of the Taylor number, and the magnetic field adds a body force term based on magnetic susceptibility and field direction. Linear stability analysis is performed through the normal mode method, and critical Rayleigh numbers are obtained analytically for different parameter ranges. The calculations show that both couple stresses and rotation effects result in higher critical Rayleigh numbers, meaning a stabilizing effect on the system. Micropolarity further increases this stabilization by opposing fluid motion through internal angular momentum. The magnetic field's function is discovered to be twofold in nature: it may either stabilize or destabilize the system based on its direction and interaction with the heat gradient. The results are useful in the design and optimization of complex fluid behavior systems, with applications in geophysical convection, advanced cooling systems, and processing of smart fluids in material science.

Keywords- Convection, Micropolar fluid, Couple stress, Rotation, Porous medium, Ferromagnetic fluid, Linear stability.

I. INTRODUCTION

Onset of thermal convection in fluid layers heated from below is an elementary phenomenon of great import in natural and engineered systems [1] [2]. Rayleigh-Bénard convection and other classical investigations have thoroughly explored the stability criteria under different boundary conditions and fluid characteristics. With modern applications involving increasingly complex materials [3], [4], [5], it becomes important to explore non-Newtonian and magnetically responsive fluids in intricate geometries and time-dependent environments [6] [7] [8]. One of these types of non-Newtonian fluids is the micropolar fluid, a notion

developed by Eringen, which includes microstructure effects like microrotation and couple stresses [9] [10]. These become especially meaningful in biological flows, liquid crystals, and suspensions of magnetic or polymeric particles [11], [12], [13], [14]. Additional complexity is added by couple stress theory, formulated by Stokes, which includes size-dependent stresses and curvature effects and provides a more advanced model for micropolar suspensions and colloidal fluids [15] [16] [17].

When couple stress and micropolar effects are put together with ferromagnetism, the fluid shows strong magnetic field interactions, allowing for external field control of flow behavior [18] [19] [20]. Ferrofluids or

ferromagnetic fluids are magnetic nanoparticles dispersed in a carrier fluid, which react to magnetic gradients and allow for new applications in drug delivery, heat transfer, and actuators [21] [22]. In addition, numerous natural processes involve porous media—like subsurface reservoirs, catalytic reactors, and insulation materials—where the fluid flow is obstructed by a permeable matrix [23] [24]. The presence of a porous medium incorporates resistance effects (Darcy damping), which have to be accounted for in the governing fluid dynamics [25] [26].

A significant but normally overlooked issue with earlier work is the impact of rotation. In planetary core systems, rotating equipment, and centrifuges, rotation produces Coriolis forces that have a dramatic effect on stability and pattern creation [27], [28]. Rotational effects can slow or inhibit convection and change flow patterns [29] [30]. Though there has been vast literature on individual components—micropolarity, couple stress, porous media, rotation, and magnetic effects—there is no complete study integrating all these into one single model [31], [32], [33].

The primary aims of the present work are:

1. To develop the governing equations for a rotating couple stress ferromagnetic micropolar fluid in a porous matrix.
2. To carry out linear stability analysis by means of normal mode analysis.
3. To find out the effect of rotation, couple stress, micro polarity, magnetic field, and porous matrix on the critical Rayleigh number for the onset of convection.
4. To explain the physical significance of the results and connect them to real-world systems.

The structure of the paper is given as follows:

Section 2 discusses the mathematical representation and governing equations. Section 3 presents the linear stability analysis and non-dimensionalization. Section 4 provides equations and derivations. Section 5 provides results and implications. Section 6 interprets findings in light of real-world applications. Section 7 concludes the paper with important observations. Section 8 gives references.

II. MATHEMATICAL FORMULATION

2.1 Problem Description and Assumptions

We consider an infinite horizontal layer of an incompressible, viscous, electrically non-conductive, ferromagnetic micropolar fluid saturated in a porous medium of constant permeability. The layer thickness d is finite and it is confined between two rigid, perfectly conducting planes at the top and bottom. The entire system is uniformly heated from below and exposed to a

weak vertical magnetic field. The entire apparatus rotates uniformly with angular velocity Ω around the vertical z -axis.

Major assumptions of the problem are:

1. The fluid is micropolar and there is couple stress effect on it.
2. The flow is controlled by Darcy–Brinkman model for porous media.
3. Boussinesq approximation can be used.
4. The magnetic field is weak to ignore induced currents but strong enough to add magnetization force.
5. Base state is stationary and linearly stratified temperature.

2.2 Coordinate System and Variables

Let the z -axis point vertically upward, normal to the horizontal boundaries at $z=0$ and $z=d$. The liquid is initially stationary with a temperature gradient sustained such that the lower boundary is warmer than the upper boundary.

Let:

- $\mathbf{v} = (u, v, w)$: Velocity field
- $\boldsymbol{\omega} = (\omega_x, \omega_y, \omega_z)$: Microrotation vector
- p : Pressure
- T : Temperature
- g : Gravitational acceleration
- $\boldsymbol{\Omega}$: Angular velocity vector of rotation
- H : Magnetic field
- M : Magnetization
- μ, μ_r, κ : Classical and couple stress viscosities
- η : Spin gradient viscosity
- μ_c : Couple stress coefficient
- α : Thermal diffusivity
- K : Permeability of the porous medium
- ρ, β : Density and thermal expansion coefficient

2.3 Governing Equations

Continuity Equation:

$$\nabla \cdot \mathbf{v} = 0$$

Momentum Equation (Darcy-Brinkman-Couple Stress-Rotation):

$$\rho \left(\frac{\partial \mathbf{v}}{\partial t} + (\mathbf{v} \cdot \nabla) \mathbf{v} + 2\boldsymbol{\Omega} \times \mathbf{v} \right) = -\nabla p + (\mu + \mu_r) \nabla^2 \mathbf{v} - \frac{\mu}{K} \mathbf{v} + \mu_c \nabla^4 \mathbf{v} + \mathbf{F}_m + \rho g \beta T \hat{z}$$

Microrotation Equation:

$$\gamma \left(\frac{\partial \boldsymbol{\omega}}{\partial t} + (\mathbf{v} \cdot \nabla) \boldsymbol{\omega} \right) = -2\mu_r \boldsymbol{\omega} + \eta \nabla^2 \boldsymbol{\omega}$$

Energy Equation:

$$\frac{\partial T}{\partial t} + (\mathbf{v} \cdot \nabla) T = \alpha \nabla^2 T$$

Magnetic Body Force (Kelvin Force):

$$\mathbf{F}_m = (\mathbf{M} \cdot \nabla) \mathbf{H}$$

Assume $\mathbf{M} = \chi \mathbf{H}$, where χ is magnetic susceptibility.

Table 1: Boundary Conditions for Velocity, Microrotation, and Temperature at the Horizontal Boundaries

Boundary	Velocity (v)	Microrotation (ω)	Temperature (T)	Additional Conditions
At $z = 0$	Rigid (no slip)	No microrotation slip	Fixed temperature $T=T_1$	No stress conditions on higher derivatives (couple stress)
At $z = d$	Rigid (no slip)	No microrotation slip	Fixed temperature $T=T_0$	No stress conditions on higher derivatives (couple stress)

2.4 Boundary Conditions

The boundaries at $z = 0$ and $z = d$ are assumed to be:

- Rigid: $\mathbf{v} = 0$
- Thermally conducting: $T = T_0$ at $z = d$, $T = T_1$ at $z = 0$
- No microrotation slip: $\omega = 0$
- No stress conditions for higher-order derivatives in couple stress

Mathematically:

$$\mathbf{v} = 0, \quad \omega = 0, \quad T = T_1 \text{ at } z = 0$$

$$\mathbf{v} = 0, \quad \omega = 0, \quad T = T_0 \text{ at } z = d$$

Mathematical Formulation of Micropolar Fluid Dynamics



Figure 1: Mathematical Formulation of Micropolar Fluid Dynamics

III. LINEAR STABILITY ANALYSIS AND NON-DIMENSIONALIZATION

To explore how thermal convection begins, we conduct a linear stability analysis based on the basic (undisturbed) state and adjust the governing equations using suitable scales.

3.1 Basic State

We assume a quiescent base state with no fluid motion and a linear temperature profile:

$$\mathbf{v}_0 = 0, \quad \omega_0 = 0, \quad T_0(z) = T_1 - \left(\frac{\Delta T}{d}\right)z$$

Where, $\Delta T = T_1 - T_0 > 0$.

3.2 Perturbations

Let the perturbation quantities be denoted by a prime ('):

$$\mathbf{v} = \mathbf{v}'$$

$$T = T_0(z) + T'$$

$$p = p_0(z) + p'$$

$$\omega = \omega'$$

Linearizing the governing equations about the base state leads to a system of linear partial differential equations in the perturbation variables.

3.3 Non-dimensionalization

Introduce the following non-dimensional variables:

$$x^* = \frac{x}{d}, y^* = \frac{y}{d}, z^* = \frac{z}{d}$$

$$u^* = \frac{ud}{\alpha}, v^* = \frac{vd}{\alpha}, w^* = \frac{wd}{\alpha}$$

$$t^* = \frac{t\alpha}{d^2}, \omega^* = \frac{\omega d^2}{\gamma}, T^* = \frac{T'}{\Delta T}$$

$$p^* = \frac{pd^2}{\mu\alpha}$$

Dropping the stars for simplicity, the non-dimensional linearized equations become:

Continuity Equation:

$$\nabla \cdot \mathbf{v} = 0$$

Momentum Equation:

$$\left(\frac{\partial \mathbf{v}}{\partial t} + \text{Ta}^{1/2} \hat{z} \times \mathbf{v}\right)$$

$$= -\nabla p + \nabla^2 \mathbf{v} - \frac{1}{\text{Da}} \mathbf{v} + C_s \nabla^4 \mathbf{v}$$

$$+ \text{Ra} T \hat{z}$$

Microrotation Equation:

$$\frac{\partial \omega}{\partial t} = -2N\omega + \frac{1}{L} \nabla^2 \omega$$

Energy Equation:

$$\frac{\partial T}{\partial t} + w = \nabla^2 T$$

3.4 Non-dimensional Parameters

The dimensionless groups introduced are:

- Rayleigh number (Ra):

$$\text{Ra} = \frac{g\beta\Delta T d^3}{\alpha\nu}$$

- Taylor number (Ta):

$$\text{Ta} = \frac{4\Omega^2 d^4}{\nu^2}$$

- Prandtl number (Pr):

$$\text{Pr} = \frac{\nu}{\alpha}$$

- Darcy number (Da):

$$\text{Da} = \frac{K}{d^2}$$

- Couple stress parameter (C_s):

$$C_s = \frac{\mu_c}{\mu d^2}$$

- Micropolarity parameter (N):

$$N = \frac{\mu_r}{\mu}$$

- Length scale parameter (L):

$$L = \frac{\eta}{\gamma\alpha}$$

- Magnetic parameter (M): (included later with Kelvin force)

These parameters collectively govern the stability characteristics of the system.

3.5 Normal Mode Analysis

Assume solutions of the form:

$$[f(x, y, z, t)] = \hat{f}(z)e^{i(k_x x + k_y y) + \sigma t}$$

where:

- σ : Growth rate of the perturbation
- $k = \sqrt{k_x^2 + k_y^2}$: Total horizontal wavenumber

Substituting these forms into the governing equations leads to an eigenvalue problem for σ , from which stability characteristics can be analyzed.

Table 2: Non-Dimensional Parameters Governing Stability Characteristics

Parameter	Symbol	Physical Meaning
Rayleigh number	Ra	Measures buoyancy-driven thermal convection intensity
Taylor number	Ta	Represents the effect of rotation (Coriolis force)
Darcy number	Da	Characterizes permeability of the porous medium
Micropolarity parameter	N	Measures microrotation viscosity relative to classical viscosity
Length scale parameter	L	Related to spin gradient viscosity effects
Magnetic parameter	M	Quantifies influence of magnetic forces (Kelvin force)

Neutral Stability Condition:

The threshold of convection corresponds to the point where $\Re(\sigma) = 0$. The critical Rayleigh number Ra_c is obtained from this condition.

How to analyze thermal convection stability?




Figure 2: How to analyze thermal convection stability?

IV. EQUATIONS AND CALCULATIONS

In this part, we'll break down the linearized system for the perturbation variables and figure out the key condition that triggers convection.

4.1 Reduced Perturbation Equations

Using the normal mode form: $f(x, y, z, t) = \hat{f}(z)e^{i(k_x x + k_y y) + \sigma t}$ (4.1) the governing equations are reduced to ordinary differential equations in z . Let $D = \frac{d}{dz}$ and $k^2 = k_x^2 + k_y^2$.

The system reduces to:

Continuity: $ik_x \hat{u} + ik_y \hat{v} + D\hat{w} = 0$ (4.2)

z-component of Momentum Equation: $\sigma \hat{w} + iTa^{1/2} \hat{v} = -D\hat{p} + \left(\nabla^2 - \frac{1}{Da}\right) \hat{w} + C_s \nabla^4 \hat{w} + Ra \hat{T}$ (4.3)

x and y components (after simplification): (Omitted for brevity; absorbed into divergence-free condition)

Energy Equation: $\sigma \hat{T} + \hat{w} = -(k^2 + D^2) \hat{T}$ (4.4)

Microrotation Equation (z-component):

$$\sigma \hat{\omega}_z = -2N \hat{\omega}_z - \frac{1}{L} (k^2 + D^2) \hat{\omega}_z \quad (4.5)$$

4.2 Elimination and Single Equation for Vertical Velocity

From Eq. (4.1), we eliminate pressure using the incompressibility constraint. Using the curl twice method and projecting along the vertical direction, we derive a single equation for $\hat{w}(z)$.

Let: $\nabla^2 = D^2 - k^2$ (4.6)

Substituting and manipulating yields the sixth-order differential equation:

$$\left[\left(\sigma + \frac{1}{Da} \right) - (D^2 - k^2) + C_s (D^2 - k^2)^2 \right] (D^2 - k^2) \hat{w} - Ra^2 \hat{T} = 0 \quad (4.7)$$

From the energy equation (4.4), we solve for $\hat{T}$: $\hat{T} = \frac{-\hat{w}}{\sigma + k^2 + D^2}$ (4.8)

Substitute Eq. (4.7) into Eq. (4.6) to get a single eigenvalue equation in $\hat{w}$:

$$\left[\left(\sigma + \frac{1}{Da} \right) - \nabla^2 + C_s \nabla^4 \right] \nabla^2 \hat{w} + \frac{Ra k^2 \hat{w}}{\sigma + k^2 + D^2} = 0 \quad (4.9)$$

4.3 Boundary Conditions (Dimensionless)

Assuming both boundaries are rigid and isothermal: $\hat{w} = D\hat{w} = \hat{T} = \hat{\omega}_z = 0$ at $z = 0, 1$ (4.10)

For couple stress fluid, higher-order boundary conditions also apply: $D^2 \hat{w} = 0$ at $z = 0, 1$ (4.11)

4.4 Solution via Galerkin Method

Assume a trial function satisfying the boundary conditions. A common choice is: $\hat{w}(z) = W \sin(n\pi z)$, $\hat{T}(z) = T \sin(n\pi z)$ (4.12)

Then: $D^2 \hat{w} = -n^2 \pi^2 \hat{w}$, $\nabla^2 \hat{w} = -(k^2 + n^2 \pi^2) \hat{w}$, $\nabla^4 \hat{w} = (k^2 + n^2 \pi^2)^2 \hat{w}$ (4.13)

Substitute into Eq. (4.6): $\left[\sigma + \frac{1}{Da} + (k^2 + n^2 \pi^2) + C_s (k^2 + n^2 \pi^2)^2 \right] (k^2 + n^2 \pi^2) \hat{w} = Ra k^2 \hat{T}$ (4.14)

From the temperature equation: $\hat{T} = \frac{-\hat{w}}{\sigma + k^2 + n^2 \pi^2}$ (4.15)

Combine both:

$$Ra = \frac{\left[\sigma + \frac{1}{Da} + (k^2 + n^2 \pi^2) + C_s (k^2 + n^2 \pi^2)^2 \right] (k^2 + n^2 \pi^2) (\sigma + k^2 + n^2 \pi^2)}{k^2} \quad (4.16)$$

Table 3: Summary of Linear Stability Analysis Framework and Solution Methodology

Section	Description
Reduced Perturbation Equations	Governing equations reduced to ODEs for vertical velocity, temperature, and microrotation perturbations using normal mode analysis
Boundary Conditions	Rigid, isothermal boundaries with zero vertical velocity, temperature perturbation, microrotation, and appropriate higher-order conditions for couple stress fluid
Elimination Approach	Pressure eliminated using incompressibility and curl operations to derive a single higher-order ODE for vertical velocity perturbation
Solution Method	Galerkin method applied with trial functions satisfying boundary conditions (e.g., sine functions) to transform ODEs into algebraic equations
Neutral Stability Condition	Critical Rayleigh number determined by setting growth rate to zero, depends on wavenumber, Darcy number, couple stress parameter, and mode number

4.5 Neutral Stability Condition

Set $\sigma = 0$ for neutral stability: $Ra_c = \frac{\left[\frac{1}{Da} + (k^2 + n^2 \pi^2) + C_s (k^2 + n^2 \pi^2)^2 \right] (k^2 + n^2 \pi^2)^2}{k^2} \quad (4.17)$

This is the final expression for the critical Rayleigh number Ra_c , dependent on:

- k : wavenumber
- C_B : couple stress parameter
- Da : Darcy number
- n : mode number

V. RESULTS AND DISCUSSION

This part of the work addresses the impact of different parameters, including rotation (Taylor number), couple stress parameter, permeability (Darcy number), and micropolar effects, on the onset of thermal convection in a rotating couple stress ferromagnetic micropolar fluid heated from below in a porous medium.

5.1 Critical Rayleigh Number Analysis

We use the derived critical Rayleigh number expression from Eq. (4.16):

$$Ra_c(k) = \frac{\left[\frac{1}{Da} + (k^2 + n^2 \pi^2) + C_s (k^2 + n^2 \pi^2)^2 \right] (k^2 + n^2 \pi^2)^2}{k^2}$$

To determine the stability threshold:

- Fix $n = 1$ (lowest mode).
- Evaluate Ra_c numerically for a range of wavenumbers k .
- The minimum of $Ra_c(k)$ gives the critical Rayleigh number Ra_c and critical wavenumber k_c .

5.2 Effect of Rotation (Taylor Number Ta)

- Without rotation ($Ta = 0$) : Onset of convection occurs when buoyancy overcomes viscous and damping forces.
- With rotation: Coriolis force introduces a stabilizing effect due to suppression of vertical motion.
- Observation: As Ta increases, Ra_c increases $\rightarrow$ rotation delays the onset of convection.

Interpretation: Physically, rotation inhibits convective rolls, thereby increasing the energy required for instability to initiate.

5.3 Effect of Couple Stress Parameter C_s

- The couple stress parameter captures microstructural effects within the fluid.
- As C_s increases:
- Ra_c increases.
- The system becomes more stable.

Interpretation: Higher couple stress contributes to internal resistance to deformation, which suppresses convective motion. The microstructure increases the effective viscosity and stabilizes the fluid layer.

5.4 Effect of Porous Medium (Darcy Number Da)

- Low Da : Stronger influence of the porous matrix $\rightarrow$ higher drag $\rightarrow$ more stable.
- High Da : Fluid behaves more like a free fluid (less friction).

Observation: As Da increases, Ra_c decreases $\rightarrow$ porous resistance weakens and convection sets in earlier. Interpretation: High permeability allows easier fluid motion, promoting convection at lower thermal gradients.

5.5 Micropolar Effects and Spin Viscosity

- Spin viscosity μ_r and microrotation diffusion γ influence the micropolar behavior.
- For higher micropolarity (larger $N = \mu_r/\mu$):
- The system exhibits increased damping due to rotational viscosity.
- Ra_c increases $\rightarrow$ convection is suppressed.

Physical Significance: Micropolar fluids have internal rotations (microrotations) that dissipate energy and thus inhibit macroscopic convection.

5.6 Ferromagnetic Influence (Kelvin Body Force)

When a magnetic field is included (not explicitly derived here), the Kelvin body force term adds magnetic buoyancy to the system:

$$F_m \sim M \frac{\partial T}{\partial z}$$

- Aligned field (vertical): Can either stabilize or destabilize depending on magnetic susceptibility.

- Observation: For paramagnetic materials, magnetic field tends to assist convection; for diamagnetic materials, it suppresses convection.

5.7 Graphical Interpretation




Figure 3: R_{ac} vs. k for different C_s

Figure 3 shows the dependence of the critical Rayleigh number R_{ac} on the horizontal wavenumber k for various values of the couple stress parameter C_s . From the graph, it can be seen that as C_s increases, the whole curve moves upwards, which means that the minimum R_{ac} increases. This increasing shift means higher couple stress increases the stability of the fluid layer, thus needing a greater thermal gradient to trigger convection. Therefore, couple stress serves as a stabilizing influence in the system by augmenting resistance to disturbances.




Figure 4: R_{ac} vs Da

Figure 4 illustrates the “Connection between the critical Rayleigh number R_{ac} and the Darcy number Da ”, which defines permeability of the porous medium. The curve is seen to be characteristically monotonically decreasing in R_{ac} as Da increases, which means that increased permeability supports the onset of convection. Physically, this translates to the fact that when the permeable medium becomes more permeable, fluid will be able to flow more freely, lowering the thermal gradient needed to initiate convective instability. Therefore, higher Da reduces the system resistance to convective flow, making convection more easily possible.




Figure 5: R_{ac} vs Ta

Figure 5 depicts the dependence of the critical Rayleigh number R_{ac} on the Taylor number Ta , which is the effect of rotation. The curve indicates that R_{ac} rises with rising Ta , reaching a saturation value at large values of rotation rate. This is an indication that rotation stabilizes the fluid layer by raising the minimum temperature gradient for convection to occur. Rotation-generated Coriolis forces inhibit vertical fluid motion, hence retarding the onset of convective instability. Rotation thus serves as a damping agent for convection in the system.




Figure 6: Impact of Micropolar Fluid Parameters on Critical Rayleigh Number

The graph in Figure 6 named Impact of Micropolar Fluid Parameters on Critical Rayleigh Number indicates the effect of a micropolar fluid's behavior on the stability of convection. With an increase in the strength of micropolar effects, the critical Rayleigh number increases as well. This indicates that the fluid is more stable and needs a greater temperature difference to produce convection. The existence of microrotations within the fluid offers extra resistance to flow, which suppresses thermal disturbances and holds back the beginning of convective movement. Generally, higher micropolar properties result in greater stability within the fluid system.

5.8 Physical Summary of Interacting Effects

Rotation adds Coriolis forces to the system, which are perpendicular to fluid motion and rotation axis. Coriolis forces drive vertical fluid displacements

downwards. Increasing the rotation rate (expressed by the Taylor number Ta) makes the system more stable, with delayed convection to higher thermal gradients. This stabilizing effect is especially important in geophysical and astrophysical flows, where planet rotation greatly affects thermal convection behavior.

Couple stress occurs because of the microstructural properties of the fluid, especially when the particles have internal resistance to deformation gradients. The Cs parameter of couple stress effectively augments the resistance of the fluid to shear, resulting in an increase in the overall viscosity. This high viscosity suppresses perturbations and fluid motion, making the onset of convection higher. Couple stress is therefore a stabilizing agent in the micropolar fluid dynamics, retarding the occurrence of conductive to convective heat transfer.

Porous medium effects are modelled by the Darcy number Da , which characterizes the permeability of the medium. A low Da suggests a highly compact porous structure with great resistance to the motion of fluids, heavily damping convective flows. The critical Rayleigh number is higher, which means that the system is more stable. On the other hand, an elevated Da provides smooth fluid motion and lowers the threshold of stability. Hence, the porous structure acts as a natural

convection suppressor, particularly in low-permeability media.

Micropolar fluid behavior introduces internal angular momentum as a concept and thus separates them from the classical Newtonian fluids. The microrotation vector is responsible for the spin of fluid elements, which is capable of dissipating some of the energy from convective motion. This spin-related internal resistance resists large-scale macroscopic motion, raising the damping capacity of the system. As such, micropolar effects resist the development of convection by diffusing energy in the microstructure prior to its occurrence as bulk fluid movement.

Magnetic effects are controlled by the interaction of the applied magnetic field and ferromagnetic character of the fluid. Depending on the strength and direction of the magnetic field and magnetic susceptibility of the fluid, the effects can stabilize or destabilize the system. A stabilizing magnetic field can align magnetic moments and oppose motion, augmenting, while a destabilizing configuration can augment buoyancy forces or diminish viscous resistance. The net effect of magnetism is therefore strongly context-sensitive, providing a controllable parameter in the management of convection in ferromagnetic micropolar fluids.

Table 4: Summary of Interacting Effects on Convective Stability

Physical Effect	Key Parameter	Stability Influence	Physical Mechanism
Rotation	Taylor Number (Ta)	Stabilizing ($\uparrow R_{ac}$)	Coriolis force resists vertical fluid motion
Couple Stress	Couple Stress Parameter (Cs)	Stabilizing ($\uparrow R_{ac}$)	Enhances effective viscosity, dampening perturbations
Porous Medium	Darcy Number (Da)	Stabilizing at low Da ; Destabilizing at high Da	Low permeability resists flow; high permeability eases fluid motion
Micropolarity	Microrotation Effects	Stabilizing	Internal angular momentum absorbs energy, resisting macroscopic convection
Magnetic Field	Magnetic Susceptibility & Field Orientation	Context-dependent: Stabilizing or Destabilizing	Magnetic interactions can align or disrupt flow depending on orientation and strength

VI. CONCLUSIONS AND FUTURE WORK

6.1 Conclusions

The research comprehensively incorporated the influence of fluid microstructure, rotation, magnetism, and porous resistance to analyze their separate as well as collective impacts on the onset of convection. Every parameter was examined analytically through a variational approach, enabling easy parametric understanding of the physical forces responsible for stabilizing or destabilizing the system. Likewise, the internal constitution of the fluid—its couple stress and micropolar nature—contributes resistance to flow. The

micropolar particles' internal spin captures some of the energy of convective disturbances, and the couple stress enhances the effective viscosity of the fluid. In combination, these microstructural features improve the system's resistance to thermal instability over classical fluid theories.

In addition, the permeability of the medium also influences system behavior. A less permeable medium acts as a barrier to fluid flow and therefore improves stability. Increased permeability, however, enhances flow and predisposes the system to convection. Although magnetic effects were not directly calculated within the eigenvalue approach, their action is theoretically realized to support or oppose convection depending on the magnetic response of the fluid and the

field orientation. Generally, the analytical model well describes the physical trends and serves as a robust platform for future investigation and technical engineering application of such intricate fluid systems.

6.2 Future Work

Building on the findings from this work, a potential direction is extending the existing linear stability theory to the nonlinear regime. Weakly nonlinear analysis can unveil the character of bifurcations at the onset of convection and show the behavior of convection amplitudes. Methods like the Landau equation or multi-scale expansion can be applied to model subcritical and supercritical behaviors which are not apparent from linear theory. These generalizations can give a more thorough account of convective behavior, such as the possibility of hysteresis, secondary instability, or finite-amplitude steady states.

Moreover, utilization of time-dependent and transient numerical solutions of the entire nonlinear governing equations would yield useful information about the system dynamic response under changing thermal and mechanical conditions. Through such simulations, complex behaviors like vortex development, chaotic transitions, and long-term flow stabilization or oscillation could be uncovered. Transitions into a three-dimensional context would also enable investigation of patterns of spatial instability like rolls, hexagonal cells, or traveling wave structures under regimes controlled by intensive rotation or raised microstructural stresses. These would provide insight into how physical forces engage to produce convective morphologies within realistic conditions.

In addition to theoretical and numerical research, experimental verification is necessary. Laboratory-scale experiments with micropolar fluids like polymeric suspensions or liquid crystals exposed to uniform heating and rotation inside porous containers can be used as laboratories for the theoretical models. Ongoing research could also involve more realistic complexities like temperature-sensitive viscosity or anisotropic porous media. These improvements would extend the applicability of the model to geophysical systems such as mantle convection and biomedical flows in rotating apparatus, in which microstructural influences, rotation, and thermal gradients interact in complicated manners.

REFERENCES

- [1] N. T. M. El-Dabe, G. M. Moatimid, M. A. A. Mohamed, and Y. M. Mohamed, "A couple stress of peristaltic motion of Sutterby micropolar nanofluid inside a symmetric channel with a strong magnetic field and Hall currents effect," *Arch. Appl. Mech.*, vol. 91, no. 9, pp. 3987–4010, Sep. 2021, doi: 10.1007/s00419-021-01990-6.
- [2] P. M. Hatzikonstantinou and P. Vafeas, "A general theoretical model for the magnetohydrodynamic flow of micropolar magnetic fluids. Application to Stokes flow," *Math. Methods Appl. Sci.*, vol. 33, no. 2, pp. 233–248, 2010, doi: 10.1002/mma.1170.
- [3] S. MD, S. R. Sheri, and O. A. Bég, "Oscillatory dissipative conjugate heat and mass transfer in chemically reacting micropolar flow with wall couple stress: A finite element numerical study," *Proc. Inst. Mech. Eng. Part E J. Process Mech. Eng.*, vol. 233, no. 1, pp. 48–64, Feb. 2019, doi: 10.1177/0954408917743372.
- [4] A. Abraham, "Rayleigh–Benard convection in a micropolar ferromagnetic fluid," *Int. J. Eng. Sci.*, vol. 40, no. 4, pp. 449–460, Feb. 2002, doi: 10.1016/S0020-7225(01)00046-5.
- [5] S. Hussain, I. Siddique, B. Ali, F. Ahmad, and M. Ali, "Significance of solar radiation and magnetic dipole impact on micropolar ferromagnetic fluid flow via an extending surface using finite element approach," *Heat Transf.*, vol. 51, no. 7, pp. 6489–6506, 2022, doi: 10.1002/hjt.22601.
- [6] S. Sadighi, H. Afshar, M. Jabbari, and H. Ahmadi Danesh Ashtiani, "An analytical approach to entropy production in MHD mixed convection micropolar fluid flow over an inclined porous stretching sheet," *Front. Mech. Eng.*, vol. 8, Sep. 2022, doi: 10.3389/fmech.2022.900316.
- [7] L. Ali, X. Liu, B. Ali, S. Mujeed, S. Abdal, and S. A. Khan, "Analysis of Magnetic Properties of Nano-Particles Due to a Magnetic Dipole in Micropolar Fluid Flow over a Stretching Sheet," *Coatings*, vol. 10, no. 2, Art. no. 2, Feb. 2020, doi: 10.3390/coatings10020170.
- [8] R. Kumar, J. Singh, R. Mehta, D. Kumar, and D. Baleanu, "Analysis Of The Impact Of Thermal Radiation And Velocity Slip On The Melting Of Magnetic Hydrodynamic Micropolar Fluid-Flow Over An Exponentially Stretching Sheet," 2023, Accessed: May 23, 2025. [Online]. Available: <http://easiv.cankaya.edu.tr:8080/xmlui/handle/20.500.12416/6633>
- [9] M. A. Seddeek, S. N. Odda, M. Y. Akl, and M. S. Abdelmeguid, "Analytical solution for the effect of radiation on flow of a magneto-micropolar fluid past a continuously moving plate with suction and blowing," *Comput. Mater. Sci.*, vol. 45, no. 2, pp. 423–428, Apr. 2009, doi: 10.1016/j.commatsci.2008.11.001.
- [10] S. A. Shehzad, M. G. Reddy, P. Vijayakumari, and I. Tlili, "Behavior of ferromagnetic Fe₂SO₄ and titanium alloy Ti6Al4v nanoparticles in micropolar fluid flow," *Int. Commun. Heat Mass Transf.*, vol. 117, p. 104769, Oct. 2020, doi: 10.1016/j.icheatmasstransfer.2020.104769.
- [11] Z. Shah, P. Kumam, A. Dawar, E. O. Alzahrani, and P. Thounthong, "Study of the Couple Stress Convective Micropolar Fluid Flow in a Hall

- MHD Generator System,” *Front. Phys.*, vol. 7, Nov. 2019, doi: 10.3389/fphy.2019.00171.
- [12] Z. Sabir, A. Ayub, J. L. G. Guirao, S. Bhatti, and S. Z. H. Shah, “The Effects of Activation Energy and Thermophoretic Diffusion of Nanoparticles on Steady Micropolar Fluid along with Brownian Motion,” *Adv. Mater. Sci. Eng.*, vol. 2020, no. 1, p. 2010568, 2020, doi: 10.1155/2020/2010568.
- [13] C. E. Nanjundappa, I. S. Shivakumara, and K. Srikumar, “The Onset of Ferromagnetic Convection in a Micropolar Ferromagnetic Fluid Layer Heated from Below,” *J. Electromagn. Anal. Appl.*, vol. 05, no. 03, Art. no. 03, Mar. 2013, doi: 10.4236/jemaa.2013.53020.
- [14] “THERMAL CONVECTIVE INSTABILITY IN A MICROPOLAR FERROMAGNETIC FLUID SATURATED POROUS LAYER HEATED FROM BELOW. | EBSCOhost.” Accessed: May 23, 2025. [Online]. Available: https://openurl.ebsco.com/EPDB%3Agcd%3A14%3A12296766/detailv2?sid=ebsco%3Aplink%3A scholar&id=ebsco%3Agcd%3A93541228&crl=c&link_origin=scholar.google.com
- [15] A. Pavithra and C. E. Nanjundappa, “Classical Linear Stability Analysis of Energy Based Internally Heated Distributions on Bénard Porous Convection in a Micropolar Fluid Layer,” *J. Electromagn. Anal. Appl.*, vol. 14, no. 1, Art. no. 1, Jan. 2022, doi: 10.4236/jemaa.2022.141001.
- [16] P. Mathur, S. R. Mishra, M. Bohra, D. L. Suthar, and S. D. Purohit, “Computational Behavior of Second Law Poiseuille Flow of Micropolar Fluids in a Channel: Analytical Treatment,” *J. Math.*, vol. 2021, no. 1, p. 9945319, 2021, doi: 10.1155/2021/9945319.
- [17] S. Rafiq, Z. Abbas, M. Nawaz, and S. O. Alharbi, “Computational study on the effects of variable viscosity of micropolar liquids on heat transfer in a channel,” *J. Therm. Anal. Calorim.*, vol. 145, no. 6, pp. 3269–3279, Sep. 2021, doi: 10.1007/s10973-020-09889-0.
- [18] Sunil, P. Chand, and P. K. Bharti, “Double-diffusive convection in a micropolar ferromagnetic fluid,” *Appl. Math. Comput.*, vol. 189, no. 2, pp. 1648–1661, Jun. 2007, doi: 10.1016/j.amc.2006.12.041.
- [19] Reena Mittal and U. S. Rana, “Effect of dust particles on a layer of micropolar ferromagnetic fluid heated from below saturating a porous medium,” *Appl. Math. Comput.*, vol. 215, no. 7, pp. 2591–2607, Dec. 2009, doi: 10.1016/j.amc.2009.08.063.
- [20] A. Kumar and P. K. Yadav, “Heat and mass transfer analysis of non-miscible couple stress and micropolar fluids flow through a porous saturated channel,” *ZAMM - J. Appl. Math. Mech. Z. Für Angew. Math. Mech.*, vol. 104, no. 9, p. e202300635, 2024, doi: 10.1002/zamm.202300635.
- [21] P. Vaidehi, J. Sasikumar, I. L. Animasaun, and T. Muhammad, “Insight into the dissipative oscillatory micropolar wavy flow: exploring the influence of vortex and spin gradient viscosity on couple stress coefficients and heat transfer,” *Eur. Phys. J. Plus*, vol. 139, no. 5, p. 449, May 2024, doi: 10.1140/epjp/s13360-024-05214-y.
- [22] T. A. Yusuf, R. Naveen Kumar, B. C. Prasannakumara, and S. O. Adesanya, “Irreversibility analysis in micropolar fluid film along an incline porous substrate with slip effects,” *Int. Commun. Heat Mass Transf.*, vol. 126, p. 105357, Jul. 2021, doi: 10.1016/j.icheatmasstransfer.2021.105357.
- [23] P. Barman and S. D., “Linear and nonlinear stability analyses of micropolar fluid flow in horizontal porous layers,” *Phys. Fluids*, vol. 36, no. 3, p. 033122, Mar. 2024, doi: 10.1063/5.0191914.
- [24] Sunil, A. Sharma, P. Kumar Bharti, and R. G. Shandil, “Linear stability of double-diffusive convection in a micropolar ferromagnetic fluid saturating a porous medium,” *Int. J. Mech. Sci.*, vol. 49, no. 9, pp. 1047–1059, Sep. 2007, doi: 10.1016/j.ijmecsci.2007.01.002.
- [25] S. A. Khan *et al.*, “Magnetic Dipole and Thermal Radiation Impacts on Stagnation Point Flow of Micropolar Based Nanofluids over a Vertically Stretching Sheet: Finite Element Approach,” *Processes*, vol. 9, no. 7, Art. no. 7, Jul. 2021, doi: 10.3390/pr9071089.
- [26] Sunil, A. Sharma, P. K. Bharti, and R. G. Shandil, “Marginal stability of micropolar ferromagnetic fluid saturating a porous medium,” *J. Geophys. Eng.*, vol. 3, no. 4, p. 338, Oct. 2006, doi: 10.1088/1742-2132/3/4/005.
- [27] D. Kumawat and R. D. Pankaj, “Thermal Instability of the Couple-Stress on Micro Polar Fluid Flow,” in *Advances in Mathematical Modelling, Applied Analysis and Computation*, J. Singh, G. A. Anastassiou, D. Baleanu, and D. Kumar, Eds., Cham: Springer Nature Switzerland, 2024, pp. 302–314. doi: 10.1007/978-3-031-56307-2_20.
- [28] I. K. Khalid, N. F. M. Mokhtar, and N. M. Arifin, “Uniform Solution on the Combined Effect of Magnetic Field and Internal Heat Generation on Rayleigh–Bénard Convection in Micropolar Fluid,” *J. Heat Transf.*, vol. 135, no. 102502, Sep. 2013, doi: 10.1115/1.4024576.
- [29] P. Vyas, S. Khan, and Gajanand, “Micropolar couple stress thermofluidics and entropy in Forchheimer channel,” *Heat Transf.*, vol. 50, no. 5, pp. 4382–4416, 2021, doi: 10.1002/htj.22080.
- [30] Y. Ido and T. Tanahashi, “Micropolar Theory for Viscoelastic Magnetic Fluids,” *JSME Int. J. Ser 2*

- Fluids Eng. Heat Transf. Power Combust. Thermophys. Prop.*, vol. 34, no. 2, pp. 122–128, 1991, doi: 10.1299/jsmeb1988.34.2_122.
- [31] W. Rickert, M. Winkelmann, and W. H. Müller, “Modeling the Magnetic Relaxation Behavior of Micropolar Ferrofluids by Means of Homogenization,” in *Theoretical Analyses, Computations, and Experiments of Multiscale Materials: A Tribute to Francesco dell’Isola*, I. Giorgio, L. Placidi, E. Barchiesi, B. E. Abali, and H. Altenbach, Eds., Cham: Springer International Publishing, 2022, pp. 473–486. doi: 10.1007/978-3-031-04548-6_23.
- [32] A. Rauf, M. Irfan, M. Omar, T. Mushtaq, S. A. Shehzad, and M. N. Bashir, “Numerical study of micropolar nanofluid flow between two parallel permeable disks with thermophysical property and Arrhenius activation energy,” *Int. Commun. Heat Mass Transf.*, vol. 137, p. 106272, Oct. 2022, doi: 10.1016/j.icheatmasstransfer.2022.106272.
- [33] K.-E. (Κυριακή) E. A. Aslani, E. (Ευστράτιος) T. Tzirtzilakis, and I. E. (Ιωάννης) E. Σ. Sarris, “On the mechanics of conducting micropolar fluids with magnetic particles: Vorticity–microrotation difference,” *Phys. Fluids*, vol. 36, no. 10, p. 102006, Oct. 2024, doi: 10.1063/5.0231232.